



MARKING

SSK HSK100A-SFH5/16CR-5.12
VR302JR 월/년0일 G2.5/25,000

- NOTE**
1. ROUND R=1.0
 2. BREAK SHARP CONERS 0.5x45°
 3. ANGLES ±0°15'
 4. BALANCE : G2.5 / 25,000rpm

MATERIAL	REV No.	00	DATE	2021.03.18	표	기	호	Rmax	-	Ra	-	Rz	-	기	본	차	구	분	1-50	50-100	100-250	250-500	DRAWN	CHECKED	CHECKED	CHECKED	APPROVED	
MAT. SIZE	SURFACE TREATMENT				면	▽	▽							내	경	외	경	전	장	±0.1	±0.15	±0.25	±0.35	Y.H.J				
HARDNESS	H _{RC}	KIND	ISO12164-1		조	▽	▽	100S	25a	63a	25Z		±0.1	±0.15	±0.25	±0.35												
DESCRIPTION	SHRINK FIT HOLDER				도	▽	▽	25S	63a	63S	1.6a	63Z	±0.1	±0.15	±0.25	±0.35												
ORDER MAKER	SAB	OEM CODE	VR302JR			▽	▽	63S	1.6a	63Z																		
SPEC.	HSK100A-SFH7.9375(5/16)CR-130(5.12)	TYPE	Machining			▽	▽	0.8S	0.2a	0.8Z																		